RPM INDUSTRIAL RUBBER PARTS


CANADA
2290 Industrial Street
Burlington, Ontario L7P 1A1


USA
4392 Broadway
Depew, NY 14043, USA

888.842.5668
905.335.5523
rpmrubberparts.com

VMC-4030IU

in Sandwich Mounts (UNC Thread) Type 4





- Compact and lightweight.
- Easy to install.
- Maintenance-free.
- Three size groups: small, medium and large.
- Unitized construction.

Rubber Flex Sandwich Mounts are designed to protect equipment and machinery against damaging vibration. This family of mounts has excellent capacity for energy control.
Constructed with high-strength bonds and specially compounded elastomers, these mounts provide high load-carrying capacity and assure long life.

The simple design and unitized construction provide low-cost mounting systems which are compact, lightweight, easy to install and maintenance-free.

These mounts are available in three size groups to suit a variety of applications. Small Rubber Flex Sandwich Mounts are available in metric and standard (UNC) threads.

Typical applications for Rubber Flex Sandwich Mounts include business machines, motorcycles, heating, ventilating and air conditioning equipment, light motors, appliances, shipping containers, feeders, compactors and vibratory rollers.

Specifications

COMPRESSION STATIC LOAD (LBS)	123
COMPRESSION STATIC LOAD (N)	549
COMPRESSION - SPRING RATE KC (LBS/IN)	31
COMPRESSION - SPRING RATE KC (N/MM)	174
SHEAR STATIC LOAD (LBS)	41
SHEAR STATIC LOAD (N)	183
SHEAR - SPRING RATE KS (LBS/IN)	6
SHEAR - SPRING RATE KS (N/MM)	34
A (IN)	1.57
B (IN)	0.31
C (IN)	1.18

DUROMETER	43
ELASTOMER	Natural Rubber
PRODUCT TYPE	Mounts
MANUFACTURER	RPM Mechanical Inc
TYPE	4
GRADE PER SAE J429	2