RPM INDUSTRIAL RUBBER PARTS

CANADA
2290 Industrial Street
Burlington, Ontario L7P 1A1


USA
4392 Broadway
Depew, NY 14043, USA

888.842.5668
905.335.5523
rpmrubberparts.com

VME-7525QU

in Sandwich Mounts (UNC Thread) Type 5





- Economical.
- Compact and lightweight.
- Easy to install.
- Maintenance-free.
- Three size groups: small, medium and large.
- Unitized construction.

RPM Mechanical's sandwich mounts are designed to be a simple and effective way to absorb energy, the resulting effect isolates and protects your equipment from damaging impact forces.

This product type can also be used as machine supports when securing your unit to a base is not required or when the base is not strong enough. Giving you a simple and effective product to isolate your equipment.

Other materials are available on request, contact our sales staff for more information.

COMPRESSION STATIC LOAD (LBS)	2333
COMPRESSION STATIC LOAD (N)	10382
COMPRESSION - SPRING RATE KC (LBS/IN)	3745
COMPRESSION - SPRING RATE KC (N/MM)	3745
A (IN)	3
B (IN)	0.47
C (IN)	1
THREAD SIZE	1/2-13 UNC
DUROMETER	68
ELASTOMER	Natural Rubber
THREAD TYPE	Standard UNC
PRODUCT TYPE	
MANUFACTURER	RPM Mechanical Inc
TYPE	5
GRADE PER SAE J429	