

J-1211-5-3 Dynaflex® Shear Type Couplings



Item # J-1211-5-3 Dynaflex® Shear Type Couplings
 Manufacturer: Parker Lord Corporation

Specifications

Bolt Thread Size	0.5
Bore Diameter (A) (in)	1/2
C (in)	1.13
D Ref (in)	1.63
E Ref (in)	1
F (in)	2.5
Horse Power (1750 RPM) (hp)	1/2
Set Screw Size	1/4 to 20
Static Torsional Stiffness (lb/in)	1.33
Torque Rating (lb-in)	20
Torque Rating (lb/in)	20
Typical Applications	20 Shear-type flexible couplings are useful in many small equipment driveline applications. Multi-directional misalignment capabilities make them ideally suited for fractional horsepower drivelines de



For Low Frequency Vibration Isolation and Misalignment Accommodation Compact, one-piece flexible couplings economically constructed to isolate low-frequency vibration and accommodate multi-directional misalignment.

Large Selection of Standard Sizes Fractional horsepower couplings are available in a range of sizes to permit matching a specific coupling to your application.



[Request for Quote](#)

[Contact Us](#)

USA
 4392 Broadway
 Depew, NY 14043

Canada
 2290 Industrial Street
 Burlington, Ontario
 L7P 1A1

888.842.5668
 905.335.5523
info@rpmrubberparts.com




torque assures excellent
vibration isolation. Specified
torque rating allows 15°
angular deflection for excellent
vibration isolation.
Max. recommended
Misalignments-1/32 in.
parallel, 2° angular.



[Request for Quote](#)


[Contact Us](#)

 **USA**
4392 Broadway
Depew, NY 14043

 **Canada**
2290 Industrial Street
Burlington, Ontario
L7P 1A1

 888.842.5668

 905.335.5523

 info@rpmrubberparts.com

