

# J-1211-6-12 Dynaflex® Shear Type Couplings



Item # J-1211-6-12 Dynaflex® Shear Type Couplings  
 Manufacturer: Parker Lord Corporation

## Specifications

Bolt Thread Size	0.5
Bore Diameter (A) (in)	1/2
C (in)	1.38
D Ref (in)	1.81
E Ref (in)	1.05
F (in)	2.69
Horse Power (1750 RPM) (hp)	3/4
Set Screw Size	5/16 to 18
Static Torsional Stiffness (lb/in)	2
Torque Rating (lb-in)	30
Torque Rating (lb/in)	30
Typical Applications	30 Shear-type flexible couplings are useful in many small equipment driveline applications. Multi-directional misalignment capabilities make them ideally suited for fractional horsepower drivelines de



**For Low Frequency Vibration Isolation and Misalignment Accommodation** Compact, one-piece flexible couplings economically constructed to isolate low- frequency vibration and accommodate multi-directional misalignment.

**Large Selection of Standard Sizes** Fractional horsepower couplings are available in a range of sizes to permit matching a specific coupling to your application. **Standard Construction** :- Hubs - steel,



[Request for Quote](#)

[Contact Us](#)

**USA**  
 4392 Broadway  
 Depew, NY 14043

**Canada**  
 2290 Industrial Street  
 Burlington, Ontario  
 L7P 1A1

888.842.5668

905.335.5523

info@rpmrubberparts.com



vibration isolation. Specified torque rating allows 15° angular deflection for excellent vibration isolation. Max. recommended Misalignments- 1/32 in. parallel, 2° angular. Non-Stock Item, please contact



[Request for Quote](#)

[Contact Us](#)

 **USA**  
4392 Broadway  
Depew, NY 14043

 **Canada**  
2290 Industrial Street  
Burlington, Ontario  
L7P 1A1

 888.842.5668

 905.335.5523

 [info@rpmrubberparts.com](mailto:info@rpmrubberparts.com)

