

J-1211-7-4 Dynaflex® Shear Type Couplings


Item # J-1211-7-4 Dynaflex® Shear Type Couplings

Manufacturer: Parker Lord Corporation



Specifications

Bolt Thread Size	0.625
Bore Diameter (A) (in)	0.75
C (in)	1.5
D Ref (in)	2
E Ref (in)	1.11
F (in)	2.88
Horse Power (1750 RPM) (hp)	1
Set Screw Size	5/16 to 18
Static Torsional Stiffness (lb/in)	2.66
Torque Rating (lb-in)	40
Torque Rating (lb/in)	40
Typical Applications	Shear-type flexible couplings are useful in many small equipment driveline applications. Multi-directional misalignment capabilities make them ideally suited for fractional horsepower drivelines de



For Low Frequency Vibration Isolation and Misalignment

Accommodation Compact, one-piece flexible couplings economically constructed to isolate low- frequency vibration and accommodate multi-directional misalignment.

Large Selection of Standard Sizes Fractional horsepower couplings are available in a


[Request for Quote](#)
[Contact Us](#)


USA

4392 Broadway
Depew, NY 14043



Canada

2290 Industrial Street
Burlington, Ontario
L7P 1A1



888.842.5668



905.335.5523



info@rpmrubberparts.com



convenient for small
equipment with fractional
horsepower requirements.
Torsional deflection at rated
torque assures excellent
vibration isolation. Specified
torque rating allows 15°
angular deflection for excellent
vibration isolation. Max.
recommended Misalignments-
1/32 in. parallel, 2° angular.
Non-Stock Item, please
contact



[Request for Quote](#)

[Contact Us](#)



USA

4392 Broadway
Depew, NY 14043



Canada

2290 Industrial Street
Burlington, Ontario
L7P 1A1



888.842.5668



905.335.5523



info@rpmrubberparts.com

