

SK-1947-29 Dynaflex® Shear Type Couplings



Item # SK-1947-29 Dynaflex® Shear Type Couplings
 Manufacturer: Parker Lord Corporation

Specifications

| | |
|------------------------------------|---|
| Bolt Thread Size | 0.25 |
| Bore Diameter (A) (in) | 1/4 |
| C (in) | 0.44 |
| D Ref (in) | 0.56 |
| E Ref (in) | 0.36 |
| F (in) | 0.81 |
| Horse Power (1750 RPM) (hp) | 1/50 |
| Set Screw Size | 5/40 |
| Static Torsional Stiffness (lb/in) | 0.053 |
| Torque Rating (lb-in) | 0.8 |
| Torque Rating (lb/in) | 0.8 |
| Typical Applications | Shear-type flexible couplings are useful in many small equipment driveline applications. Multi-directional misalignment capabilities make them ideally suited for fractional horsepower drivelines de |



For Low Frequency Vibration Isolation and Misalignment Accommodation Compact, one-piece flexible couplings economically constructed to isolate low- frequency vibration and accommodate multi-directional misalignment.

Large Selection of Standard Sizes Fractional horsepower couplings are available in a range of sizes to permit matching a specific coupling to your application. **Standard Construction** :- Hubs - steel,



[Request for Quote](#)

[Contact Us](#)

USA
 4392 Broadway
 Depew, NY 14043

Canada
 2290 Industrial Street
 Burlington, Ontario
 L7P 1A1

888.842.5668
 905.335.5523
info@rpmrubberparts.com



vibration isolation. Specified torque rating allows 15° angular deflection for excellent vibration isolation. Max. recommended Misalignments- 1/32 in. parallel, 2° angular.



[Request for Quote](#)


[Contact Us](#)

 **USA**
4392 Broadway
Depew, NY 14043

 **Canada**
2290 Industrial Street
Burlington, Ontario
L7P 1A1

 888.842.5668

 905.335.5523

 info@rpmrubberparts.com

