

# SK-1947 Dynaflex® Shear Type Couplings



**Item #** SK-1947 Dynaflex® Shear Type Couplings  
**Manufacturer:** Parker Lord Corporation

## Specifications

<b>Bolt Thread Size</b>	<b>0.187</b>
<b>Bore Diameter (A) (in)</b>	<b>0.187</b>
<b>Bore Diameter (B) (in)</b>	<b>0.187</b>
<b>C (in)</b>	<b>0.44</b>
<b>D Ref (in)</b>	<b>0.56</b>
<b>E Ref (in)</b>	<b>0.36</b>
<b>F (in)</b>	<b>0.81</b>
<b>Horse Power (1750 RPM) (hp)</b>	<b>1/50</b>
<b>Set Screw Size</b>	<b>5/40</b>
<b>Static Torsional Stiffness (lb/in)</b>	<b>0.053</b>
<b>Torque Rating (lb-in)</b>	<b>0.8</b>
<b>Torque Rating (lb/in)</b>	<b>0.8</b>
<b>Typical Applications</b>	<b>Shear-type flexible couplings are useful in many small equipment driveline applications. Multi-directional misalignment capabilities make them ideally suited for</b>



**For Low Frequency Vibration Isolation and Misalignment Accommodation** Compact, one-piece flexible couplings economically constructed to isolate low- frequency vibration and accommodate multi-directional misalignment.

**Large Selection of Standard Sizes** Fractional horsepower couplings are available in a range of sizes to permit matching a specific coupling to your application. **Standard Construction** :- Hubs - steel,



[Request for Quote](#)

[Contact Us](#)

**USA**  
 4392 Broadway  
 Depew, NY 14043

**Canada**  
 2290 Industrial Street  
 Burlington, Ontario  
 L7P 1A1

888.842.5668  
 905.335.5523  
[info@rpmrubberparts.com](mailto:info@rpmrubberparts.com)



vibration isolation. Specified torque rating allows 15° angular deflection for excellent vibration isolation. Max. recommended Misalignments- 1/32 in. parallel, 2° angular.



[Request for Quote](#)


[Contact Us](#)

 **USA**  
4392 Broadway  
Depew, NY 14043

 **Canada**  
2290 Industrial Street  
Burlington, Ontario  
L7P 1A1

 888.842.5668

 905.335.5523

 [info@rpmrubberparts.com](mailto:info@rpmrubberparts.com)

