Spec Sheets

VMA-2513AU Sandwich Mounts Unc Thread Type 1



Item # VMA-2513AU Sandwich Mounts Unc Thread Type 1
Manufacturer: RPM Mechanical Inc

Specifications

A (in)	1
B (in)	0.75
C (in)	0.5
Compression Spring Rate Kc (Imperial)	2364
Compression Spring Rate Kc (Metric)	418
Compression Static Load (lbs)	122
Compression Static Load (Metric)	545
D (in)	0.75
Durometer	57
Elastomer	Natural Rubber
Grade per SAE J429	1
Manufacturer	RPM Mechanical Inc.
Shear Spring Rate Ks (lbs/in)	348



Request for Quote

Contact Us

USA
4392 Broadway
Depew, NY 14043

Canada
2290 Industrial Street
Burlington, Ontario
L7P 1A1

888.842.5668
905.335.5523
info@rpmrubberparts.com

Spec Sheets

VMA-2513AU Sandwich Mounts Unc Thread Type 1



Item # VMA-2513AU Sandwich Mounts Unc Thread Type 1
Manufacturer: RPM Mechanical Inc

Specifications (Continued)

Shear Spring Rate Ks (Metric)	**62**
Shear Static Load (lbs)	**40**
Shear Static Load (Metric)	**182**
Thread Size	**1/4-20 UNC**
Thread Type	**Standard UNC**
Types	**1**



RPM INDUSTRIAL RUBBER PARTS

Request for Quote

Contact Us

USA
4392 Broadway
Depew, NY 14043

Canada
2290 Industrial Street
Burlington, Ontario
L7P 1A1

888.842.5668
905.335.5523
info@rpmrubberparts.com