


VMA-3015AU Sandwich Mounts Unc Thread Type 1



Item # VMA-3015AU Sandwich Mounts Unc Thread Type 1
Manufacturer: RPM Mechanical Inc

Specifications

A (in)	1.18
B (in)	0.75
C (in)	0.59
Compression Spring Rate Kc (Imperial)	2460
Compression Spring Rate Kc (Metric)	961
Compression Static Load (lbs)	162
Compression Static Load (Metric)	1386
D (in)	0.75
Durometer	57
Elastomer	Natural Rubber
Grade per SAE J429	1
Manufacturer	RPM Mechanical Inc.
Shear Spring Rate Ks (lbs/in)	383


[Request for Quote](#)
[Contact Us](#)

USA
 4392 Broadway
 Depew, NY 14043

Canada
 2290 Industrial Street
 Burlington, Ontario
 L7P 1A1

888.842.5668

905.335.5523

info@rpmrubberparts.com



VMA-3015AU Sandwich Mounts Unc Thread Type 1



Item # VMA-3015AU Sandwich Mounts Unc Thread Type 1
Manufacturer: RPM Mechanical Inc

Specifications (Continued)

Shear Spring Rate Ks (Metric)	68
Shear Static Load (lbs)	54
Shear Static Load (Metric)	241
Thread Size	5/16-18 UNC
Thread Type	Standard UNC
Types	1



[Request for Quote](#)

[Contact Us](#)

USA
4392 Broadway
Depew, NY 14043

Canada
2290 Industrial Street
Burlington, Ontario
L7P 1A1

888.842.5668

905.335.5523

info@rpmrubberparts.com

