



VMA-1045KU

in Sandwich Mounts (UNC Thread) Type 1



- Economical.
- Compact and lightweight.
- Easy to install.
- Maintenance-free.
- Three size groups: small, medium and large.
- Unitized construction.

high load-carrying capacity and assure long life.

The simple design and unitized construction provide low-cost mounting systems which are compact, lightweight, easy to install and maintenance-free.

These mounts are available in three size groups to suit a variety of applications. Small Rubber Flex Bobbin Sandwich Mounts are available in metric and standard (UNC) threads.

Typical applications for Rubber Flex Bobbin Sandwich Mounts include business machines, motorcycles, heating, ventilating and air conditioning equipment, light motors, appliances, shipping containers, feeders, compactors and vibratory rollers.

Specifications

COMPRESSION STATIC LOAD (LBS)	2905
COMPRESSION STATIC LOAD (N)	12928
COMPRESSION - SPRING RATE KC (LBS/IN)	13162
COMPRESSION - SPRING RATE KC (N/MM)	2329
SHEAR STATIC LOAD (LBS)	968
SHEAR STATIC LOAD (N)	4309
SHEAR - SPRING RATE KS (LBS/IN)	2045
SHEAR - SPRING RATE KS (N/MM)	364
A (IN)	4
B (IN)	1.77
C (IN)	1.77
D (IN)	1.77
THREAD SIZE	5/8-11 UNC
DUROMETER	68
ELASTOMER	Natural Rubber
THREAD TYPE	Standard UNC
PRODUCT TYPE	Mounts

TYPE	1
GRADE PER SAE J429	1