RPM INDUSTRIAL RUBBER PARTS

CANADA
2290 Industrial Street
Burlington, Ontario L7P 1A1

USA
4392 Broadway
Depew, NY 14043, USA

888.842.5668
905.335.5523
rpmrubberparts.com

VMA-1080GU

in Sandwich Mounts (UNC Thread) Type 1



- Economical.
- Compact and lightweight.
- Easy to install.
- Maintenance-free.
- Three size groups: small, medium and large.
- Unitized construction.

high load-carrying capacity and assure long life.

The simple design and unitized construction provide low-cost mounting systems which are compact, lightweight, easy to install and maintenance-free.

These mounts are available in three size groups to suit a variety of applications. Small Rubber Flex Bobbin Sandwich Mounts are available in metric and standard (UNC) threads.

Typical applications for Rubber Flex Bobbin Sandwich Mounts include business machines, motorcycles, heating, ventilating and air conditioning equipment, light motors, appliances, shipping containers, feeders, compactors and vibratory rollers.

Specifications

COMPRESSION STATIC LOAD (LBS)	665
COMPRESSION STATIC LOAD (N)	2961
COMPRESSION - SPRING RATE KC (LBS/IN)	1533
COMPRESSION - SPRING RATE KC (N/MM)	274
SHEAR STATIC LOAD (LBS)	221
SHEAR STATIC LOAD (N)	987
SHEAR - SPRING RATE KS (LBS/IN)	351
SHEAR - SPRING RATE KS (N/MM)	62
A (IN)	4
B (IN)	1.77
C (IN)	3.15
D (IN)	1.77
THREAD SIZE	5/8-11 UNC
DUROMETER	43
ELASTOMER	Natural Rubber
THREAD TYPE	Standard UNC
PRODUCT TYPE	Mounts

TYPE	1
GRADE PER SAE J429	1