


VMA-7535K

in Sandwich Mounts (Metric Thread) Type 1



- Economical.
- Compact and lightweight.
- Easy to install.
- Maintenance-free.
- Three size groups: small, medium and large.
- Unitized construction.

Constructed with high-strength bonds and specially compounded elastomers, these mounts provide high load-carrying capacity and assure long life.

The simple design and unitized construction provide low-cost mounting systems which are compact, lightweight, easy to install and maintenance-free.

These mounts are available in three size groups to suit a variety of applications. Small Rubber Flex Bobbin Sandwich Mounts are available in metric and standard (UNC) threads.

Typical applications for Rubber Flex Bobbin Sandwich Mounts include business machines, motorcycles, heating, ventilating and air conditioning equipment, light motors, appliances, shipping containers, feeders, compactors and vibratory rollers.

Specifications

COMPRESSION STATIC LOAD (LBS)	1583
COMPRESSION STATIC LOAD (N)	7041
COMPRESSION - SPRING RATE KC (LBS/IN)	9137
COMPRESSION - SPRING RATE KC (N/MM)	1619
SHEAR STATIC LOAD (LBS)	528
SHEAR STATIC LOAD (N)	2347
SHEAR - SPRING RATE KS (LBS/IN)	1470
SHEAR - SPRING RATE KS (N/MM)	261
A (IN)	3
B (IN)	1.46
C (IN)	1.38
D (IN)	1.46
THREAD SIZE	M12
DUROMETER	68
ELASTOMER	Natural Rubber
THREAD TYPE	Metric

TYPE	1
GRADE PER SAE J429	4.6